

ALARIS

ALARIS REELS FEATURE:

- Multi-disc, Japanese oiled felt drag washers
- 3BB+1RB stainless steel bearings
- Quick-Set ant-reverse bearing
- Precision machine cut brass pinion gear
- Corrosion resistant graphite body and rotor
- CFR: Cyclonic Flow Rotor technology
- Rigid metal handle design for strength
- Machined aluminum, 2-tone anodized spool with LCS lip
- Corrosion-resistant stainless steel bail wire
- RESII: Computer balanced Rotor Equalizing System



ALS-30

ALARIS

	Model	Gear ratio	Bearings	Weight (g)	Line retrieve(cm)	Max Drag Force (kg)	Monofilament line capacity (diameter in mm.)	Frame	Sideplates	Rotor	Spool	
	Standard speed spinning reels											
NEW	ALS-20	4.8:1	3BB+1RB	204	60.7	5.4	0.15/250, 0.20/140, 0.25/90	GR	GR	GR	AL	
NEW	ALS-30	5.0:1	3BB+1RB	237	70.7	7.2	0.20/300, 0.25/200, 0.30/130	GR	GR	GR	AL	
NEW	ALS-40	5.0:1	3BB+1RB	260	84.8	7.9	0.25/260, 0.30/180, 0.35/130	GR	GR	GR	AL	
NEW	ALS-50	5.0:1	3BB+1RB	250	85.0	8	0.30/230, 0.35/170, 0.40/130	GR	GR	GR	AL	

Model: ALS-40 Wide Rotor

AURA

AURA REELS FEATURE:

- Multi-disc, Japanese oiled felt drag washers
- 1BB+1RB ball bearings
- Quick-Set ant-reverse bearing
- Precision machine cut brass pinion gear
- Corrosion resistant graphite body and rotor
- CFR: Cyclonic Flow Rotor technology
- Machined aluminum anodized spool with LCS lip
- Corrosion-resistant stainless steel bail wire
- RESII: Computer balanced Rotor Equalizing System



Aura-30

AURA

	Model	Gear ratio	Bearings	Weight (g)	Line retrieve(cm)	Max Drag Force (kg)	Monofilament line capacity (diameter in mm.)	Frame	Sideplates	Rotor	Spool	
	Standard speed spinning reels											
NEW	Aura-20	4.8:1	1BB+1RB	190	60.7	5.4	0.15/250, 0.20/140, 0.25/90	GR	GR	GR	AL	
NEW	Aura-30	5.0:1	1BB+1RB	215	70.7	7.2	0.20/300, 0.25/200, 0.30/130	GR	GR	GR	AL	
NEW	Aura-40	5.0:1	1BB+1RB	242	84.8	7.9	0.25/260, 0.30/180, 0.35/130	GR	GR	GR	AL	
NEW	Aura-50	5.0:1	1BB+1RB	235	84.8	8.0	0.30/230, 0.35/170, 0.40/130	GR	GR	GR	AL	