

ANDROS

ANDROS SINGLE-SPEED REELS FEATURE:

- High Speed 6.4:1 gear ratio
- 6-pcs ABEC-5 rated Japanese ball bearings
- Dual anti-reverse system.(Mechanical and roller bearing)
- Ratchet drag lever for precise drag settings
- Ergo grip handle knob with anodized aluminum handle arm
- One screw right sideplate take down for easy internal access
- 17-4 grade stainless steel helical cut gearing
- Maximum drag at Full with complete freespool is 11 kg
- Maximum drag at Strike with complete freespool is 9 kg
- Carbonite drag system with Cal's drag grease
- Integrated recessed reel foot design for low profile rod fit



A-12S



A-5NS



A-5S



ANDROS SINGLE-SPEED LEVER DRAGS

Model	Gear ratios	Bearings	Weight (g)	Line retrieve(cm)	Monofilament line capacity (diameter in mm.)	Max Drag @ Strike with Freespool	Max Drag @ Full with Freespool	Frame	Sideplates	Spool
Single-speed lever drag reels										
A-5NS	6.4:1	6BB + 1RB	440	106.9	0.32/385, 0.37/275, 0.42/225	7 kg	11 kg	AL	AL	AL
A-5S	6.4:1	6BB + 1RB	440	106.9	0.32/570, 0.37/400, 0.42/320	7 kg	11 kg	AL	AL	AL
A-12S	6.4:1	6BB + 1RB	669	122.9	0.42/510, 0.48/380, 0.55/290	12 kg	15 kg	AL	AL	AL