

Carbonite I

CARBONITE I REELS FEATURE:

- 1 ball bearing drive system for smoothness
- Quick-Set anti-reverse roller bearing
- Corrosion-resistant graphite body
- Precision Elliptical Gearing System
- Regular handle
- Regular graphite spool
- Durable stainless steel bail wire
- RESII: Computer-balanced Rotor Equalizing System



CBR-235

CARBONITE I

Model	Gear ratio	Bearings	Weight (g)	Line retrieve (cm)	Max Drag Force (kg)	Monofilament line capacity (diameter in mm.)	Frame	Sideplates	Rotor	Spool
CBR-225	5.0:1	1BB+1RB	220	68.6	4	0.15/360, 0.20/210, 0.25/140	GR	GR	GR	GR
CBR-230	5.0:1	1BB+1RB	220	68.6	4	0.20/240, 0.25/155, 0.30/110	GR	GR	GR	GR
CBR-235	5.0:1	1BB+1RB	280	71.1	5	0.25/230, 0.30/165, 0.35/120	GR	GR	GR	GR
CBR-240	5.0:1	1BB+1RB	285	71.1	5	0.25/300, 0.30/210, 0.35/155	GR	GR	GR	GR

COMPRESSA

COMPRESSA REELS FEATURE:

- 3 ball bearings
- Aluminum spool
- Regular handle
- Spare spool



CP-30



CPR-30

COMPRESSA

Model	Gear ratio	Bearings	Weight (g)	Line retrieve (cm)	Max Drag Force (kg)	Monofilament line capacity (diameter in mm.)	Frame	Sideplates	Rotor	Spool	Extra Spool
Compressa -Front Drag											
CP-30	5.0:1	3BB	250	70.6	5	0.20/360, 0.25/230, 0.30/160	GR	GR	GR	AL	GR
CP-40	4.5:1	3BB	340	71.1	7	0.30/270, 0.35/200, 0.40/150	GR	GR	GR	AL	GR
CP-50	4.5:1	3BB	390	78.7	7	0.35/300, 0.40/230, 0.50/140	GR	GR	GR	AL	GR
CP-65	4.5:1	3BB	545	91.4	12	0.35/410, 0.40/320, 0.50/200	GR	GR	GR	AL	GR
CP-80	4.5:1	3BB	585	101.6	12	0.45/320, 0.50/260, 0.55/220	GR	GR	GR	AL	GR
Compressa-Rear Drag											
CPR-20	5.0:1	3BB	240	66.0	2.5	0.15/340, 0.18/240, 0.20/200	GR	GR	GR	AL	GR
CPR-30	5.0:1	3BB	250	70.6	2.5	0.20/360, 0.25/230, 0.30/160	GR	GR	GR	AL	GR
CPR-40	4.5:1	3BB	340	71.4	5	0.30/270, 0.35/200, 0.40/150	GR	GR	GR	AL	GR
CPR-50	4.5:1	3BB	390	79.8	5	0.35/300, 0.40/230, 0.50/140	GR	GR	GR	AL	GR