

CERROS®

CERROS LOW PROFILE BAITCAST REELS FEATURE:

- ALC: Rigid diecast aluminum frame
- A6061-T6 machined aluminum, anodized V-shaped spool
- Multi-disc composite drag system
- 9BB + 1RB bearings drive system
- Micro-click drag star for precise drag settings
- External adjustable magnetic cast control system
- 24-point adjustment on cast control for precise settings
- Quick-Set anti-reverse roller bearing
- Corrosion resistant graphite side plates
- Side plate access port for quick spool changes
- Light weight and comfortable EVA handle knobs
- Available in both right and left hand retrieve



CR-266V



CERROS LOWPROFILES

Model	Gear ratio	Bearings	Weight (g)	Line retrieve (cm)	Max Drag Force (kg)	Monofilament line capacity (diameter in mm.)	Frame	Right Sideplate	Left Sideplate	Spool
Right handed lowprofile baitcast reels										
CR-266V	6.6:1	9BB+1RB	238	80.3	5	0.29/145, 0.33/118, 0.37/86	AL	GR	GR	AL
Left handed lowprofile baitcast reels										
CR-266VLX	6.6:1	9BB+1RB	238	80.3	5	0.29/145, 0.33/118, 0.37/86	AL	GR	GR	AL

TORMENTA

TORMENTA LOW PROFILE BAITCAST REELS FEATURE:

- Corrosion resistant graphite frame and sideplates
- A6061-T6 machined aluminum, anodized U-shaped spool
- Multi-disc composite drag system
- 2BB+1RB bearings drive system
- Micro-click drag star for precise drag settings
- External adjustable magnetic cast control system
- Quick-Set anti-reverse roller bearing
- Easy change palm sideplate access port
- Ergonomic handle design allows cranking closer to body
- Zirconium line guide inserts for use with braided line
- Available gear ratio: 6.6:1
- Available in both right and left hand retrieve



Tt-266WLX



TORMENTA LOWPROFILES

Model	Gear ratio	Bearings	Weight (g)	Line retrieve (cm)	Max Drag Force (kg)	Monofilament line capacity (diameter in mm.)	Frame	Right Sideplate	Left Sideplate	Spool
Right handed lowprofile baitcast reels										
Tt-266W	6.6:1	2BB+1RB	227	72.4	5	0.29/145, 0.33/118, 0.37/86	GR	GR	GR	AL
Left handed lowprofile baitcast reels										
Tt-266WLX	6.6:1	2BB+1RB	227	72.4	5	0.29/145, 0.33/118, 0.37/86	GR	GR	GR	AL