



CXT-40



CXTR-40

# Ceymar XT

## CETMAR XT REELS FEATURE:

- Multi-disc, Japanese oiled felt drag system
- 7BB+1RB for ultimate smoothness, 6BB+1RB on size 10
- Quick-Set anti-reverse roller bearing
- Precision machine cut brass pinion gear
- Corrosion-resistant graphite body
- Rigid, forged zinc, black anodized handle design
- Light weight, TPE handle knobs for comfort
- Precision Elliptical Gearing system
- Machined aluminum, 2-tone anodized spool
- Heavy duty, solid aluminum bail wire
- RESII: Computer balanced Rotor Equalizing System
- Line control system on the spool for better line casting
- Alum handle with EVA knob
- Plastic line clip
- Spare aluminum spool



## CEYMAR XT

Model	Gear ratio	Bearings	Weight (g)	Line retrieve (cm)	Max Drag Force (kg)	Monofilament line capacity (diameter in mm.)	Frame	Sideplates	Rotor	Spool	Extra Spool	
Ceymar XT -Front Drag												
CXT-10	5.0:1	6BB+1RB	170	55.4	3	0.10/260, 0.14/150, 0.16/115	GR	GR	GR	AL	AL	
CXT-25	5.0:1	7BB+1RB	227	65.5	3	0.15/295, 0.20/170, 0.25/110	GR	GR	GR	AL	AL	
CXT-30	5.0:1	7BB+1RB	232	65.5	3	0.20/200, 0.25/130, 0.30/100	GR	GR	GR	AL	AL	
CXT-35	5.0:1	7BB+1RB	269	76.2	6	0.25/195, 0.30/135, 0.35/100	GR	GR	GR	AL	AL	
CXT-40	5.0:1	7BB+1RB	283	76.2	6	0.25/240, 0.30/170, 0.35/125	GR	GR	GR	AL	AL	
CXT-55	4.5:1	7BB+1RB	403	79.0	9	0.30/325, 0.35/240, 0.40/185	GR	GR	GR	AL	AL	
CXT-65	4.8:1	7BB+1RB	586	97.3	11	0.35/340, 0.40/265, 0.50/160	GR	GR	GR	AL	AL	
Ceymar XT -Rear Drag												
CXTR-30MS	6.2:1	7BB+1RB	227	65.5	3	0.12/320, 0.15/210, 0.18/150	GR	GR	GR	AL	AL	
CXTR-30	5.0:1	7BB+1RB	232	65.5	3	0.20/200, 0.25/130, 0.30/100	GR	GR	GR	AL	AL	
CXTR-40MS	6.2:1	7BB+1RB	269	76.2	6	0.15/210, 0.20/120, 0.25/80	GR	GR	GR	AL	AL	
CXTR-40	5.0:1	7BB+1RB	283	76.2	6	0.25/240, 0.30/170, 0.35/125	GR	GR	GR	AL	AL	