

Ceymar

CEYMAR LOWPROFILE BAITCAST REELS FEATURE:

- Corrosion-resistant graphite frame and side plates
- A6061-T6 machined aluminum, anodized U-shaped spool
- Multi-disc composite drag system
- 6BB+1RB bearing drive system
- External adjustable magnetic cast control system
- Quick-Set anti-reverse roller bearing
- Side plate access port for quick spool changes
- Ergonomic handle design allows cranking closer to body
- Available gear ratio: 6.6:1



C-266W



CEYMAR LOWPROFILES

Model	Gear ratio	Bearings	Weight (g)	Line retrieve (cm)	Max Drag Force (kg)	Monofilament line capacity (diameter in mm.)	Frame	Right Sideplate	Left Sideplate	Spool
C-266W	6.6:1	6BB+1RB	215	72.4	5	0.29/140, 0.33/120, 0.37/85	GR	GR	GR	AL
C-266WLX	6.6:1	6BB+1RB	215	72.4	5	0.29/140, 0.33/120, 0.37/85	GR	GR	GR	AL

CITRIX

CITRIX 350-SIZE REELS FEATURE:

- ALC: Rigid diecast aluminum frame and handle side plate
- A6061-T6 machined aluminum, anodized V-shaped spool
- Multi-disc Carbonite drag system
- 7BB+1RB bearings drive system
- Micro-click drag star for precise drag settings
- External adjustable centrifugal cast control system
- Quick-Set anti-reverse roller bearing
- Graphite sideplates
- Easy change palm side plate access port
- Ergonomic handle design allows cranking closer to body
- Zirconium line guide inserts for use with braided line
- Available gear ratios: 6.4:1
- 6.4:1 gear ratio available in left hand retrieve



Ci-364a



CITRIX LOWPROFILES

Model	Gear ratio	Bearings	Weight (g)	Line retrieve (cm)	Max Drag Force (kg)	Monofilament line capacity (diameter in mm.)	Frame	Right Sideplate	Left Sideplate	Spool
Citrix 350										
Ci-364a	6.4:1	7BB+1RB	312	78.7	11	0.33/250, 0.37/230, 0.41/150	AL	AL	GR	AL
Ci-364LXa	6.4:1	7BB+1RB	312	78.7	11	0.33/250, 0.37/230, 0.41/150	AL	GR	AL	AL