



Coronado
CDX

Coronado CDX

CORONADO CDX BAITFEEDER REELS FEATURE:

- On/Off auto trip bait feeding system
- DFD: Precision Dual Force Drag system
- Carbonite drag washers on Dual Force Drag
- Heavy duty, brass DFD and spool shaft stabilizer
- 4HPB+1RB corrosion resistant stainless steel bearings
- Quick-Set ant-reverse bearing allows for zero back play in handle
- CRC: Corrosion-Resistant Coating process
- Machined aluminum, screw in handle system
- Slow oscillation system for improved line lay
- Corrosion resistant graphite body and rotor
- CFR: Cyclonic Flow Rotor technology
- Hydro Block water tight drag seal
- Machined aluminum, 2-tone anodized spool with LCS lip
- Heavy duty solid aluminum bail wire
- RESII: Computer balanced Rotor Equalizing System



CDX-60



BAITFEEDING SYSTEM:

Okuma's baitfeeding system allows anglers to disengage their spinning reel spool and allow their bait to run freely. The baitfeeding system incorporates a secondary micro-adjustable drag system at the rear of the reel that allows for precise adjustment of the spool for bait control. In order to disengage this system simply turn the handle. The On/Off lever on the rear of the reel will automatically disengage the baitfeeding system so you can fight your fish with the main drag system.



CORONADO CDX

	Model	Gear ratio	Bearings	Weight (g)	Line retrieve (cm)	Max Drag Force (kg)	Monofilament line capacity (diameter in mm.)	Braided line rating (Tuf line)	Frame	Sideplates	Rotor	Spool
	Standard speed spinning reels											
NEW	CDX-55	4.4 : 1	4HPB+1RB	550	82.6	12.7	0.30/320,0.35/230,0.40/180	245/50	GR	GR	GR	AL
NEW	CDX-60	4.4 : 1	4HPB+1RB	563	86.7	12.2	0.30/375,0.35/275,0.40/210	290/50	GR	GR	GR	AL
NEW	CDX-65	4.9 : 1	4HPB+1RB	822	106.0	15.3	0.40/300,0.45/235,0.50/190	315/65	GR	GR	GR	AL
NEW	CDX-80	4.9 : 1	4HPB+1RB	855	115.3	17	0.40/380,0.45/300,0.50/240	235/80	GR	GR	GR	AL