



Inspira

INSPIRA SPINNING REELS FEATURE:

- Light weight C-40X carbon frame and sideplates
- 8BB + 1RB stainless steel bearings
- Quick-Set anti-reverse roller bearing
- Precision machine cut brass pinion gear
- Rigid, forged aluminum, anodized handle
- Light weight, EVA handle knobs for comfort
- Precision Elliptical Gearing system
- Machined aluminum, 2-tone anodized spool
- Heavy duty, solid aluminum bail wire
- CFR: Cyclonic Flow Rotor



INSPIRA

Model	Gear ratio	Bearings	Weight (g)	Line retrieve (cm)	Max Drag Force (kg)	Monofilament line capacity (diameter in mm.)	Frame	Sideplates	Rotor	Spool
Inspira Red version with C-40X finish										
ISX-20R	5.0:1	8BB+1RB	182	60.7	3	0.15/240, 0.20/140, 0.25/90	C-40X	C-40X	GR	AL
ISX-30R	5.0:1	8BB+1RB	213	68.6	6	0.20/300, 0.25/200, 0.30/130	C-40X	C-40X	GR	AL
ISX-40R	5.0:1	8BB+1RB	268	76.2	6	0.25/260, 0.30/180, 0.35/130	C-40X	C-40X	GR	AL
Inspira Blue version with C-40X finish										
ISX-20B	5.0:1	8BB+1RB	182	60.7	3	0.15/240, 0.20/140, 0.25/90	C-40X	C-40X	GR	AL
ISX-30B	5.0:1	8BB+1RB	213	68.6	6	0.20/300, 0.25/200, 0.30/130	C-40X	C-40X	GR	AL
ISX-40B	5.0:1	8BB+1RB	268	76.2	6	0.25/260, 0.30/180, 0.35/130	C-40X	C-40X	GR	AL
Inspira White version										
ISX-20W	5.0:1	8BB+1RB	182	60.7	3	0.15/240, 0.20/140, 0.25/90	C-40X	C-40X	GR	AL
ISX-30W	5.0:1	8BB+1RB	213	68.6	6	0.20/300, 0.25/200, 0.30/130	C-40X	C-40X	GR	AL
ISX-40W	5.0:1	8BB+1RB	268	76.2	6	0.25/260, 0.30/180, 0.35/130	C-40X	C-40X	GR	AL