



KOMODO[®] SS

KOMODO SS LOW PROFILE BAITCAST REELS FEATURE:

- Stainless steel main gear for ultimate power and strength
- Precision machine cut stainless steel pinion gear
- Heavy duty stainless steel drive and spool shafts
- ALC: Rigid diecast aluminum frame and sideplates
- CRC: Corrosion-Resistant Coating process
- A6061-T6 machined aluminum, anodized spool
- Multi-disc high output Carbonite drag system
- Micro-click drag star for precise drag settings
- 350 size: 6HPB+1RB corrosion resistant stainless steel bearings
- 450 size: 7HPB+1RB corrosion resistant stainless steel bearings
- Precision Japanese ABEC-5 spool bearings
- Dual anti-reverse for maximum reliability
- Quick-Set anti-reverse roller bearing
- 6-pin Velocity Control casting system
- Synchronized levelwind optimized for braided line
- Zirconium line guide inserts for use with braided line
- Available in both right and left hand retrieve
- On/Off clicker for trolling, chunking or bait fishing



KDS-463P



KDS-463LX



KOMODO SS LOWPROFILES

	Model	Gear ratio	Bearings	Weight (g)	Line retrieve (cm)	Max Drag Force (kg)	Monofilament line capacity (diameter in mm.)	Frame	Right Sideplate	Left Sideplate	Spool
	Komodo SS Right hand retrieve with twin paddle handle										
NEW	KDS-364	6.4:1	6HPB+1RB	310	78.7	11	0.33/250, 0.37/230, 0.41/150	AL	AL	AL	AL
	KDS-463	6.3:1	7HPB + 1RB	453	85.1	14	0.37/265, 0.42/200, 0.55/115	AL	AL	AL	AL
	Komodo SS Right hand retrieve with power handle										
NEW	KDS-364P	6.4:1	6HPB+1RB	329	78.7	11	0.33/250, 0.37/230, 0.41/150	AL	AL	AL	AL
	Komodo left hand retrieve models with twin paddle handle										
NEW	KDS-364LX	6.4:1	6HPB+1RB	310	78.7	11	0.33/250, 0.37/230, 0.41/150	AL	AL	AL	AL
	KDS-463LX	6.3:1	7HPB + 1RB	453	85.1	14	0.37/265, 0.42/200, 0.55/115	AL	AL	AL	AL