



**METALOID LEVER DRAG REELS FEATURE:**

- Rigid 1-pcs frame and left sideplate construction
- 6061-T6 Machined aluminum frame and sideplates
- Cold forged, Type-II anodized, machined aluminum spool
- CRC: Corrosion Resistant Coating process
- Available in both 2-speed or single speed versions
- 4 BB corrosion resistant stainless steel bearings
- Ergo Grip handle knob with anodized aluminum handle arm
- 17-4 grade stainless steel helical cut gearing
- Silent retrieve system for cranking smoothness
- Carbonite drag system with Cal's drag grease
- All models feature durable Ergo grip handle knobs
- On/Off bait clicker for all models



**METALOID**

Model	Gear ratios	Bearings	Weight (g)	Line retrieve(cm)	Monofilament line capacity (diameter in mm.)	Max Drag @ Strike with Freespool	Max Drag @ Full with Freespool	Frame	Side plates	Spool
<b>Metaloid single speed</b>										
M-5NS	6.4:1	4BB	420	106.9	0.32/385, 0.37/275, 0.42/225	7 kg	11 kg	AL	AL	AL
M-5S	6.4:1	4BB	440	106.9	0.32/570, 0.37/400, 0.42/320	7 kg	11 kg	AL	AL	AL
M-12S	6.4:1	4BB	669	122.9	0.42/510, 0.48/380, 0.55/290	9 kg	12 kg	AL	AL	AL
<b>Metaloid two speed</b>										
M-5NII	6.4:1 & 3.8:1	4BB	448	106.9 & 63	0.32/385, 0.37/275, 0.42/225	7 kg	11 kg	AL	AL	AL
M-5II	6.4:1 & 3.8:1	4BB	468	106.9 & 63	0.32/570, 0.37/400, 0.42/320	7 kg	11 kg	AL	AL	AL
M-12NII	4.7:1 & 2.1:1	4BB	655	90 & 40	0.42/300, 0.48/200, 0.55/150	9 kg	12 kg	AL	AL	AL
M-12II	4.7:1 & 2.1:1	4BB	680	90 & 40	0.42/510, 0.48/380, 0.55/290	9 kg	12 kg	AL	AL	AL
<b>Metaloid two speed Left Hand Retrieve</b>										
M-5IILX	6.4:1 & 3.8:1	4BB	468	106.9 & 63	0.32/570, 0.37/400, 0.42/320	7 kg	11 kg	AL	AL	AL
<b>NEW</b> M-5NIIILX	6.4:1 & 3.8:1	4BB	448	106.9 & 63	0.32/385, 0.37/275, 0.42/225	7 kg	11 kg	AL	AL	AL
M-12IILX	4.7:1 & 2.1:1	4BB	680	90 & 40	0.42/510, 0.48/380, 0.55/290	9 kg	12 kg	AL	AL	AL

# METALOID

## METALOID LEVER DRAG REELS FEATURE:

- Rigid 1-pcs frame and left sideplate construction
- 6061-T6 Machined aluminum frame and sideplates
- Cold forged, Type-II anodized, machined aluminum spool
- CRC: Corrosion Resistant Coating process
- Two-speed models now available in Red and Blue versions
- 4 BB corrosion resistant stainless steel bearings
- Ergo Grip handle knob with anodized aluminum handle arm
- 17-4 grade stainless steel helical cut gearing
- Silent retrieve system for cranking smoothness
- Carbonite drag system with Cal's drag grease
- All models feature durable Ergo grip handle knobs
- On/Off bait clicker for all models



TROLLING REELS



M-5IIB



M-5IIR



\* B represents blue version, R represents red version

## METALOID

Model	Gear ratios	Bearings	Weight (g)	Line retrieve(cm)	Monofilament line capacity (diameter in mm.)	Max Drag @ Strike with Freespool	Max Drag @ Full with Freespool	Frame	Side plates	Spool
Metaloid Two Speed										
M-5IIR	6.4:1 & 3.8:1	4BB	468	106.9 & 63	0.42/510, 0.48/380, 0.55/290	7 kg	11 kg	AL	AL	AL
M-5IIB	6.4:1 & 3.8:1	4BB	468	106.9 & 63	0.32/570, 0.37/400, 0.42/320	7 kg	11 kg	AL	AL	AL
M-12IIR	4.7:1 & 2.1:1	4BB	680	90 & 40	0.42/510, 0.48/380, 0.55/290	9 kg	12 kg	AL	AL	AL
M-12IIB	4.7:1 & 2.1:1	4BB	680	90 & 40	0.42/510, 0.48/380, 0.55/290	9 kg	12 kg	AL	AL	AL