

# Pulzar

## PULZAR REELS FEATURE:

- Multi-disc, oiled felt drag washers
- 5BB+1RB bearings drive system
- Quick-Set anti-reverse roller bearing
- Corrosion-resistant graphite body
- Machined aluminum, 2-tone anodized, ported spool
- RESII: Computer-balanced Rotor Equalizing System
- Precision Elliptical Gearing System
- Metal line clip
- LCS line control spool
- Metal handle with EVA knob
- Spare aluminum spool



PZ-25a



## PULZAR

Model	Gear ratio	Bearings	Weight (g)	Line retrieve (cm)	Max Drag Force (kg)	Monofilament line capacity (diameter in mm.)	Frame	Sideplates	Rotor	Spool	Extra Spool
PZ-10a	5.0:1	5BB+1RB	170	53.3	4	0.10/260, 0.14/150, 0.16/115	GR	GR	GR	AL	AL
PZ-25a	5.0:1	5BB+1RB	227	63.5	6.2	0.15/360, 0.20/210, 0.25/140	GR	GR	GR	AL	AL
PZ-30a	5.0:1	5BB+1RB	232	63.5	6.2	0.20/240, 0.25/155, 0.30/110	GR	GR	GR	AL	AL
PZ-40a	5.0:1	5BB+1RB	283	73.7	9	0.25/300, 0.30/210, 0.35/155	GR	GR	GR	AL	AL
PZ-55a	4.5:1	5BB+1RB	403	76.2	9.2	0.30/380, 0.35/280, 0.40/215	GR	GR	GR	AL	AL

# CUSTOM SPIN

## CUSTOM SPIN REELS FEATURE:

- Multi-disc, Japanese oiled felt drag system
- 5+1BB bearings drive system, 4+1BB on size 10
- Quick-Set anti-reverse roller bearing
- Precision machine cut brass pinion gear
- Corrosion-resistant graphite body
- Precision Elliptical Gearing System
- Machined aluminum, 2-tone anodized spool
- RESII: Computer-balanced Rotor Equalizing System
- Metal line clip
- Metal handle with EVA knob
- LCS line control spool



CSP-30



## CUSTOM SPIN

Model	Gear ratio	Bearings	Weight (g)	Line retrieve (cm)	Max Drag Force (kg)	Monofilament line capacity (diameter in mm.)	Frame	Sideplates	Rotor	Spool
CSP-10	5.0:1	4BB+1RB	171	55.4	3	0.10/260, 0.14/150, 0.16/115	GR	GR	GR	AL
CSP-25	5.0:1	5BB+1RB	230	65.5	3	0.15/360, 0.20/210, 0.25/140	GR	GR	GR	AL
CSP-30	5.0:1	5BB+1RB	230	65.5	3	0.20/240, 0.25/155, 0.30/110	GR	GR	GR	AL
CSP-40	5.0:1	5BB+1RB	270	76.2	6	0.25/300, 0.30/210, 0.35/135	GR	GR	GR	AL
CSP-55	4.5:1	5BB+1RB	360	79.0	9	0.30/380, 0.35/280, 0.40/215	GR	GR	GR	AL
CSP-65	4.8:1	5BB+1RB	575	97.3	11	0.35/390, 0.40/300, 0.50/185	GR	GR	GR	AL
CSP-80	4.8:1	5BB+1RB	600	106.7	11	0.45/305, 0.50/250, 0.55/205	GR	GR	GR	AL