

RAW-II 1002

RAW-1002 FLOAT REELS FEATURE:

- Precision 6061-T6 machined aluminum frame and spool
- Durable Type-II, two-tone anodized frame and spool
- 2 premium stainless steel Japanese ball bearings
- Machine cut stainless steel spool shaft
- 1-pcs Machined Rigid Frame construction
- On/Off click ratchet for added spool tension
- Ported spool with exposed rim for easy spool control
- Includes Okuma's protective neoprene reel shield
- RAWII is backed by a one year limited warranty



RAW-1002



RAW-463

RAW-II 463

RAW-463 MOOCKING REELS FEATURE:

- Precision 6061-T6 machined aluminum frame and spool
- Durable Type-II, two-tone anodized frame and spool
- CRC: Corrosion resistant coating process
- Multi-disc Carbonite and stainless steel drag system
- Unique lever drag system for setting downrigger baits
- Machine cut stainless steel spool shaft
- 1-pcs Machined Rigid Frame construction
- 3 precision stainless steel ball bearings
- Easy-to-change left to right hand retrieval conversion
- Includes Okuma's protective neoprene reel shield

RAW II / RAW-463

Model	Bearings	Weight (g)	Line Retrieve	Line capacity (yds/lbs)	Frame	Spool	Spool Width	Spool Diam.
Centerpin Float Reel								
RAW-1002	2 BB	233	13"	275/-yds / 8-lbs	AL	AL	18.5mm	114mm
Moocking Reel								
RAW-463	3BB	482	13"	400/-yds / 30-lbs	AL	AL	25.4mm	116mm