



### SLV FLY REELS FEATURE:

- Lightweight graphite construction
- 4-piece rod design
- Titanium Oxide stripper guide
- Stainless steel snake guides
- Aluminum pipe reel seat with aluminum hoods
- Through-blank carbon fiber construction
- Okuma rod bag



SLV-56

### SLV

Model	Line Weight	Bearings	Weight (g)	Line Retrieve	Fly line capacity	Frame	Spool	Spool Width	Spool Diam.
SLV 23	2,3 wt.	1RB	128	8"	WF-2, 50yds/12lbs	AL	AL	22mm	66mm
SLV 45	4,5 wt.	1RB	136	9"	WF-4, 95yds/12lbs	AL	AL	24mm	75mm
SLV 56	5,6 wt.	1RB	150	10"	WF-5, 140yds/20lbs	AL	AL	28mm	82mm
SLV 78	7,8 wt.	1RB	156	11"	WF-7, 145yds/20lbs	AL	AL	31mm	88mm
SLV 89	8,9 wt.	1RB	173	12"	WF-8, 150yds/30lbs	AL	AL	34mm	95mm
SLV-1011	10,11 wt.	1RB	275	13"	WF-10, 520yds/30lbs	AL	AL	40mm	114mm
Spare spools									
SLV 23 Spool	2,3 wt.	1RB	57	8"	WF-2, 50yds/12lbs	N/A	AL	22mm	66mm
SLV 45 Spool	4,5 wt.	1RB	60	9"	WF-4, 95yds/12lbs	N/A	AL	24mm	75mm
SLV 56 Spool	5,6 wt.	1RB	65	10"	WF-5, 140yds/20lbs	N/A	AL	28mm	82mm
SLV 78 Spool	7,8 wt.	1RB	71	11"	WF-7, 145yds/20lbs	N/A	AL	31mm	88mm
SLV 89 Spool	8,9 wt.	1RB	82	12"	WF-8, 150yds/30lbs	N/A	AL	34mm	95mm
SLV-1011 Spool	10,11 wt.	1RB	139	13"	WF-10, 520yds/30lbs	N/A	AL	40mm	114mm

## Integrity b

### INTEGRITY B FLY REELS FEATURE:

- Multi-disc cork drag system
- Roller bearing engages drag system in one direction
- Precision machined stainless steel spool shaft
- ALC: Alumilite diecast aluminum frame design
- Rigid diecast aluminum, large arbor spool design
- Precision machined, brass bushing drive
- Easy-to-change left to right hand retrieval conversion



I-5/6b

### INTEGRITY "B"

Model	Line Weight	Bearings	Weight (oz.)	Line Retrieve	Fly line capacity	Frame	Spool	Spool Width	Spool Diam.
I-5/6b	5,6 wt.	1RB	7.0	9"	WF-5, 70yds/12lbs	AL	AL	25mm	76mm
I-7/8b	7,8 wt.	1RB	7.5	9"	WF-7, 50yds/20lbs	AL	AL	30mm	76mm
I-8/9b	8,9 wt.	1RB	8.0	10"	WF-8, 100yds/20lbs	AL	AL	30mm	87mm
I-10/11b	10,11 wt.	1RB	8.5	12"	WF-10, 170yds/30lbs	AL	AL	30mm	99mm
Spare spools									
I-5/6b Spool	5,6 wt.	1RB	3.2	9"	WF-5, 70yds/12lbs	N/A	AL	25mm	76mm
I-7/8b Spool	7,8 wt.	1RB	3.4	9"	WF-7, 50yds/20lbs	N/A	AL	30mm	76mm
I-8/9b Spool	8,9 wt.	1RB	3.9	10"	WF-8, 100yds/20lbs	N/A	AL	30mm	87mm
I-10/11b Spool	10,11 wt.	1RB	4.4	12"	WF-10, 170yds/30lbs	N/A	AL	30mm	99mm