

SLX

SLX RODS FEATURE:

- Responsive and durable 24-ton carbon blank construction
- Split handle ferrule connection, for natural bending and easy transportation.
- Anti-tangle stainless steel guides frames.
- Zirconium guides inserts reduce friction from braided lines.
- Machined aluminum reel seat with extra locking nut.
- Spilt EVA handle design.
- Durable non-skid, rubber gimbal.
- High quality cloth bag package.



SLX

	Model	Rod Power	Length	Sections	Line Wt. (lbs)	Foregrip length	Reargrip Length	Number of Guide	Handle Style	Weight (g)
NEW	SLX-C-682ML	ML	6'8"	2-pcs	4-6	220mm	375mm	7+TIP	A	283
NEW	SLX-C-682M	M	6'8"	2-pcs	8-12	220mm	375mm	7+TIP	A	295
NEW	SLX-C-682MH	MH	6'8"	2-pcs	16-20	220mm	375mm	7+TIP	A	320

SLX BOAT

SLX BOAT RODS FEATURE:

- E-glass blank construction for maximum durability
- Heavy duty double foot guide frame.
- Polished titanium oxide guide inserts.
- Aluminum reel seat with extra locking nut.
- EVA fore and rear grips for maximum durability.
- Special cutting flat design on fore grip on application.
- Machined aluminum gimbal with EVA cap.
- High strength quality cloth bag package.



SLX BOAT

	Model	Rod Power	Length	Sections	Line Wt.(kg)	Foregrip length	Reargrip Length	Number of Guide	Handle Style	Weight (g)
NEW	SLX-C-701MH	MH	7'0"	1-pcs	10-15	350mm	275mm	8+TIP	A	467
NEW	SLX-C-561MH-15	MH	5'6"	1-pcs	15	390mm	345mm	6+TIP	A	598
NEW	SLX-C-561H-24	H	5'6"	1-pcs	24	390mm	345mm	6+TIP	A	649
NEW	SLX-C-561H-24R	H	5'6"	1-pcs	24	390mm	345mm	6+R TIP	A	667

Remark : R=Roller Tip

