



okuma

okuma

TESORO 12S

TESORO

TESORO

TESORO STAR DRAG REELS FEATURE:

- High Speed 6.2:1 gear ratio
- 6061-T6 machined aluminum frame, sideplate and spool
- 17-4 grade stainless steel helical cut gearing
- Multi-disc Carbonite drag system with Cal's drag grease
- CRC: Corrosion-Resistant Coating Process
- Swept aluminum star for increased ergonomics
- Anodized aluminum swept handle reduces wobble while cranking
- 4BB+1RB corrosion resistant bearings, spool bearing with TSI oil
- Ergo grip handle knob with anodized aluminum handle arm
- Dual anti-reverse (mechanical and roller bearing)
- XL Gearing: Drop down gear box
- Quick-Set ant-reverse bearing allows for zero back play in handle
- MSS: Mechanical Stabilizing System for increased durability
- Self-lubricating gear system, all models



TSR-10S



TSR-10S



TSR-12S



TESORO STAR DRAG REELS

Model	Gear ratio	Bearings	Weight (g)	Line retrieve (cm)	Max Drag Forcr (kg)	Monofilament line capacity (diameter in mm.)	Braided line rating (Tuf line)	Frame	Sideplates	Spool
NEW TSR-5S	6.2:1	4BB+1RB	320	99.1	7	0.35/325,0.40/255,0.45/190	N/A	AL	AL	AL
NEW TSR-10S	6.2:1	4BB+1RB	540	116.8	10	0.35/390,0.40/290,0.45/225	495/50	AL	AL	AL
NEW TSR-12S	6.2:1	4BB+1RB	550	116.8	10	0.40/375,0.45/270,0.54/170	475/65	AL	AL	AL