

X-SPOT

X-SPOT REELS FEATURES:

- 2 Stainless steel bearings
- Quick-Set anti reverse one way bearing
- Machine cut anodized aluminum spool
- 3 metal line-clips
- Regular aluminum handle with T-shape knob
- Line control system on the spool provides better line-lay
- Even flow roller
- Worm shaft transmission system



X-SPOT

X-SPOT

Model	Gear ratio	Bearings	Weight (g)	Line retrieve(cm)	Max Drag Force (kg)	Monofilament line capacity (diameter in mm.)	Frame	Sideplates	Rotor	Spool	Extra Spool
X-SPOT	5.1:1	2BB+1RB	570	128.3	8	0.25/820, 0.30/575, 0.35/430, 0.40/330	GR	GR	GR	AL	GR

DISTANCE SURF

DISTANCE SURF REELS FEATURE:

- 6 sealed ball bearings
- Quick-Set anti-reverse one way bearing
- Rotor Equalizing System
- Even flow roller
- Aluminum spool
- Extra spool
- Aluminum handle
- Carbon washer



DS-60

DISTANCE SURF

Model	Gear ratio	Bearings	Weight (g)	Line retrieve (cm)	Max Drag Force (kg)	Monofilament line capacity (diameter in mm.)	Frame	Sideplates	Rotor	Spool	Extra Spool
DS-60	4.5:1	6BB+1RB	580	100.3	12	0.25/600, 0.30/420, 0.35/310, 0.40/240	GR	GR	GR	AL	GR
DS-80	3.8:1	6BB+1RB	605	92.5	13	0.25/820, 0.30/575, 0.35/430, 0.40/330	GR	GR	GR	AL	GR

DISTANCE CARP INTR

DISTANCE CARP INTR REELS FEATURE:

- 9 sealed ball bearings
- Quick-Set anti-reverse one way bearing
- Rotor Equalizing System
- Even flow roller
- Aluminum spool
- Extra spool
- Aluminum handle
- Carbon washer



DCI-80

DISTANCE CARP INTR

Model	Gear ratio	Bearings	Weight (g)	Line retrieve(cm)	Max Drag Force (kg)	Monofilament line capacity (diameter in mm.)	Frame	Sideplates	Rotor	Spool
DCI-60	4.5:1	9BB+1RB	570	100.3	12	0.25/600, 0.30/420, 0.35/310, 0.40/240	GR	GR	GR	AL
DCI-80	3.8:1	9BB+1RB	570	92.5	13	0.25/820, 0.30/575, 0.35/430, 0.40/330	GR	GR	GR	AL